

INFINITY AURA DOLOMITE (H) *Stone, Marble*



PART NUMBER
MB1796-INAU00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
11.25" X 11.25"=0.88 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY AURA DOLOMITE WITH TULIP BLACK (H) *Stone, Marble*



PART NUMBER
MB1796-INAU01

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
11.25" X 11.25"=0.88 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY AURA FRENCH VANILLA WITH TULIP BLACK (H) *Stone, Marble*



PART NUMBER
MB1229-INAU00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
11.25" X 11.25"=0.88 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY SUN DOLOMITE (H) *Stone, Marble*



PART NUMBER
MB1796-SUN000

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
11.9" X 11.9"=0.99 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY SUN TULIP BLACK WITH DOLOMITE (H) *Stone, Marble*



PART NUMBER
MB1187-SUN000

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
11.9" X 11.9"=0.99 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY SUN FRENCH VANILLA WITH TULIP BLACK (H) *Stone, Marble*



PART NUMBER
MB1229-SUN000

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
11.9" X 11.9"=0.99 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY CONVEX DOLOMITE (H) *Stone, Marble*



PART NUMBER
MB1796-CNVX00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
10.08" X 11.66"=0.82 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY CONVEX TULIP BLACK (H) *Stone, Marble*



PART NUMBER
MB1187-CNVX00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
10.08" X 11.66"=0.82 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY INTUITION DOLOMITE (H) *Stone, Marble*



PART NUMBER
MB1796-INTU00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
9.14" X 9.14"=0.58 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY INTUITION TULIP BLACK (H) *Stone, Marble*



PART NUMBER
MB1187-INTU00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
9.14" X 9.14"=0.58 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY MATRIX DOLOMITE (H) *Stone, Marble*



PART NUMBER
MB1796-MTRX00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
11.61" X 11.93"=0.94 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY MATRIX TULIP BLACK (H & P) *Stone, Marble*



PART NUMBER
MB1187-MTRX00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
11.61" X 11.93"=0.94 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot. note: all honed and polished pieces are placed at a randomized configuration. there are 18 different faces for this item. there are no instances in which three honed or three polished pieces are put side by side within one mosaic sheet.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY MOMENT FRENCH VANILLA WITH DOLOMITE & TULIP BLACK (H) *Stone, Marble*



PART NUMBER
MB1229-MMNT00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
10.78" X 12.95" = 0.97 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY MOMENT TULIP BLACK (H, P & SB) *Stone, Marble*



PART NUMBER	PROFILE	AVAILABILITY
MB1187-MMNT00	MOSAIC	IN STOCK
GROUT JOINT	DIMENSIONS	THICKNESS
1/8"	10.78" X 12.95" = 0.97 SQFT	3/8"
ORIGIN		
Turkey		

NOTES
Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY VORTEX DOLOMITE (H) *Stone, Marble*



PART NUMBER
MB1796-VRTX00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
7.72" X 10.04" = 0.54 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

INFINITY VORTEX TULIP BLACK (H) *Stone, Marble*



PART NUMBER
MB1187-VRTX00

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
7.72" X 10.04" = 0.54 SQFT

THICKNESS
3/8"

ORIGIN
Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP	INTERIOR
Residential and Light Commercial	Non Freeze/Thaw, Wall only	No	Yes	Yes	No	Wall and Floor

SHOWER

Wall and Floor, Including Steam Showers

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.