

statements | TILE & STONE

Abaco

Porcelain Tile

Thickness: 8.7mm

of Faces: 12x24 - 20 Faces | 24x48 - 10 Faces

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	<=0.5%
Break Strength	C648	ISO-10545/4	Min. 450
Scratch Hardness	MOH's Scale	EN-101	7
Chemical Resistance	C650	ISO-10545/13	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant
Fire Rating	E84	ISO-13501/1	Non Combustable
Deep Abrasion-Unglazed Tiles	C1243	ISO-10545/6	Pass
Minimum Bond Strength (PSI)	C482	-	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42 ; >=0.5 (In&Out)
Shade and Texture Rating	CTDA "V"	-	V3
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188