

# statements | TILE & STONE

## Block

Ceramic Wall Tile  
Thickness: 8.7mm

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	>10%
Break Strength	C648	ISO-10545/4	Meets or Exceeds
Chemical Resistance	C650	ISO-10545/13	Unaffected
Shade and Texture Rating	CTDA "V"	-	V1
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone  
17600 W Valley Hwy  
Tukwilla, WA 98188

# statements | TILE & STONE

## Block

Porcelain Tile

Thickness: 9.5mm (4x24), 9mm (Hexagon)

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	<=0.5%
Break Strength	C648	ISO-10545/4	Min. 290
Scratch Hardness	MOH's Scale	EN-101	5
Chemical Resistance	C650	ISO-10545/13	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant
PEI-Abrasion Resistance of Glazed Tile	C1027	ISO-10545/7	1-5*
Minimum Bond Strength (PSI)	C482	-	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42
Shade and Texture Rating	CTDA "V"	-	V1
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

\*PEI is 1 for Azul, Verde and Negro, 4 for Gris and 5 fir Blanco

Statements Tile & Stone

17600 W Valley Hwy

Tukwilla, WA 98188