

statements | TILE & STONE

Glocal

Porcelain Tile

Thickness: 9mm

of Faces: 12x24 - 60-82 Faces | 24x24 - 30-41 Faces

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	$\leq 0.1\%$
Break Strength	C648	ISO-10545/4	$S \geq 2.500 \text{ N}$ $R \geq 48 \text{ N/mm}^2$
Chemical Resistance	C650	ISO-10545/13	UA ULA UHA
Frost Resistance	C1026	ISO-10545/12	Resistant
Stain Resistance	C1378	ISO-10545/14	5
Deep Abrasion-Unglazed Tiles	C1243	ISO-10545/6	$< 150\text{mm}^3$
Dynamic Coefficient of Friction (DCOF)	A137.1	-	> 0.42
Facial Dimensions	C499	ISO-10545/2	$\pm 0.3\%$
Range of Thickness	C499	ISO-10545/2	$\pm 5.0\%$
Warpage/Surface Flatness	C485	ISO-10545/2	$\pm 0.4\%$
Wedging/Rectangularity	C502	ISO-10545/2	$\pm 0.3\%$

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188