

# MANISON 30" X 30" HALL (M) *Porcelain*



PART NUMBER  
PO1832-303000

AVAILABILITY  
IN STOCK

DIMENSIONS  
29.53" x 29.53" = 6.055 sqft

THICKNESS  
3/8"

PROFILE  
TILES,LARGE FORMAT

VARIATION  
V4

GROUT JOINT  
1/16"

SEALER  
NOT REQUIRED, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	0.20%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	□ 35 N/mm2 Compliant	UNE-ENISO-10545-4
Thermal Expansion	ISO 10545-10 □ 0.01 %□(0.1 mm/m)	□ 7 · MK-1
Thermal Shock Resistance	Compliant	UNE-ENISO-10545-9
Frost resistance	Compliant	UNE-ENISO-10545-12
Chemical resistance	Resistant	UNE-ENISO-10545-13
Stain resistance	CLASS 5	UNE-ENISO-10545-14
DCOF	>0.42 wet	ANSI A137.1
TRAFFIC	Standard Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# MANISON 30" X 30" LIBRARY (M) *Porcelain*



PART NUMBER  
PO1833-303000

AVAILABILITY  
IN STOCK

DIMENSIONS  
29.53" x 29.53" = 6.055 sqft

THICKNESS  
3/8"

PROFILE  
TILES,LARGE FORMAT

VARIATION  
V4

GROUT JOINT  
1/16"

SEALER  
NOT REQUIRED, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	0.20%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	□ 35 N/mm2 Compliant	UNE-ENISO-10545-4
Thermal Expansion	ISO 10545-10 □ 0.01 %-(0.1 mm/m)	□ 7 · MK-1
Thermal Shock Resistance	Compliant	UNE-ENISO-10545-9
Frost resistance	Compliant	UNE-ENISO-10545-12
Chemical resistance	Resistant	UNE-ENISO-10545-13
Stain resistance	CLASS 5	UNE-ENISO-10545-14
DCOF	>0.42 wet	ANSI A137.1
TRAFFIC	Standard Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# MANISON 30" X 30" LOUNGE (M) *Porcelain*



PART NUMBER  
PO1834-303000

AVAILABILITY  
IN STOCK

DIMENSIONS  
29.53" x 29.53" = 6.055 sqft

THICKNESS  
3/8"

PROFILE  
TILES,LARGE FORMAT

VARIATION  
V4

GROUT JOINT  
1/16"

SEALER  
NOT REQUIRED, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	0.20%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	□ 35 N/mm2 Compliant	UNE-ENISO-10545-4
Thermal Expansion	ISO 10545-10 □ 0.01 %□(0.1 mm/m)	□ 7 · MK-1
Thermal Shock Resistance	Compliant	UNE-ENISO-10545-9
Frost resistance	Compliant	UNE-ENISO-10545-12
Chemical resistance	Resistant	UNE-ENISO-10545-13
Stain resistance	CLASS 5	UNE-ENISO-10545-14
DCOF	>0.42 wet	ANSI A137.1
TRAFFIC	Standard Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# MANSION 30" X 30" ARCADE (M) *Porcelain*



PART NUMBER  
PO1830-303000

AVAILABILITY  
IN STOCK

DIMENSIONS  
29.53" x 29.53" = 6.055 sqft

THICKNESS  
3/8"

PROFILE  
TILES,LARGE FORMAT

VARIATION  
V4

GROUT JOINT  
1/16"

SEALER  
NOT REQUIRED, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	0.20%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	□ 35 N/mm2 Compliant	UNE-ENISO-10545-4
Thermal Expansion	ISO 10545-10 □ 0.01 %□(0.1 mm/m)	□ 7 · MK-1
Thermal Shock Resistance	Compliant	UNE-ENISO-10545-9
Frost resistance	Compliant	UNE-ENISO-10545-12
Chemical resistance	Resistant	UNE-ENISO-10545-13
Stain resistance	CLASS 5	UNE-ENISO-10545-14
DCOF	>0.42 wet	ANSI A137.1
TRAFFIC	Standard Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# MANSION 30" X 30" COURT (M) *Porcelain*



PART NUMBER  
PO1831-303000

AVAILABILITY  
IN STOCK

DIMENSIONS  
29.53" x 29.53" = 6.055 sqft

THICKNESS  
3/8"

PROFILE  
TILES,LARGE FORMAT

VARIATION  
V4

GROUT JOINT  
1/16"

SEALER  
NOT REQUIRED, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	0.20%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	□ 35 N/mm2 Compliant	UNE-ENISO-10545-4
Thermal Expansion	ISO 10545-10 □ 0.01 %-(0.1 mm/m)	□ 7 · MK-1
Thermal Shock Resistance	Compliant	UNE-ENISO-10545-9
Frost resistance	Compliant	UNE-ENISO-10545-12
Chemical resistance	Resistant	UNE-ENISO-10545-13
Stain resistance	CLASS 5	UNE-ENISO-10545-14
DCOF	>0.42 wet	ANSI A137.1
TRAFFIC	Standard Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).