

statements | TILE & STONE

Marble Dolomita

Porcelain Tile & Ceramic Tile

Thickness: 7mm

Number of Faces: 12x24 - 52 Faces | 24x48 - 12 Faces | Suite 12x24 - 5 Faces

Porcelain

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≤0.5%
Break Strength	C648	ISO-10545/4	≥350
Scratch Hardness	MOH's Scale	EN-101	3
Chemical Resistance	C650	ISO-10545/13	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant
Fire Rating	E84	ISO-13501/1	Non-Combustible
PEI-Abrasion Resistance of Glazed Tile	C1027	ISO-10545/7	PEI 5
Minimum Bond Strength (PSI)	C482	-	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	≥0.50
Shade and Texture Rating	CTDA "V"	-	V3
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Ceramic

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≥10%
Break Strength	C648	ISO-10545/4	≥250
Scratch Hardness	MOH's Scale	EN-101	5
Chemical Resistance	C650	ISO-10545/13	Unaffected
Shade and Texture Rating	CTDA "V"	-	V3
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188