

statements | TILE & STONE

Nyuma

Porcelain Tile

Thickness: 9mm

of Faces: 12x24 - 68 Faces | 24x24 - 34 Faces

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≤ 0.1%
Break Strength	C648	ISO-10545/4	S ≥ 2.400 N R ≥ 48 N/mm ²
Chemical Resistance	C650	ISO-10545/13	A LA HA
Frost Resistance	C1026	ISO-10545/12	Resistant
Stain Resistance	C1378	ISO-10545/14	5
Fire Rating	E84	ISO-13501/1	Non-Combustible
Deep Abrasion-Unglazed Tiles	C1243	ISO-10545/6	< 150 mm ³
Dynamic Coefficient of Friction (DCOF)	A137.1	-	≥ 0.42 R10
Shade and Texture Rating	CTDA "V"	-	V3
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188