

---

## ORIGAMI BUROKKU ASH GRAY (P) *Stone, Marble*



PART NUMBER  
**MB1809-BURO00**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**8.12" x 7.10" = .297 sqft**

THICKNESS  
**3/8"**

PROFILE  
**MOSAICS**

VARIATION  
**MEDIUM**

GROUT JOINT  
**1/16"**

SEALER  
**YES**

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when properly sealed	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

---

## ORIGAMI BUROKKU WHITE HAZE (P) *Stone, Marble*



PART NUMBER  
**MB1741-BURO00**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**8.12" x 7.10" = .297 sqft**

THICKNESS  
**3/8"**

PROFILE  
**MOSAICS**

GROUT JOINT  
**1/16"**

SEALER  
**YES**

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

For detailed installation instructions, visit [akdo.com](http://akdo.com).

**ORIGAMI BUROKKU CREAM TAUPE (P)** *Stone, Marble*



PART NUMBER	PROFILE
<b>MB1716-BURO00</b>	<b>MOSAICS</b>
AVAILABILITY	VARIATION
<b>IN STOCK</b>	<b>MEDIUM</b>
DIMENSIONS	GROUT JOINT
<b>8.12" x 7.10" = .297 sqft</b>	<b>1/16"</b>
THICKNESS	SEALER
<b>3/8"</b>	<b>YES</b>

**ENVIRONMENTS**

WALL	FLOOR	INTERIOR	EXTERIOR	STEAM	WET	POOL	REPEAT
			FREEZE/THAW	SHOWER	AREA		
Yes	Yes	Yes	No	No	<small>Recommended for wet area walls only, if sealed properly.</small>	No	No

**TECHNICAL DATA**

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	standard commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT. CREAM TAUPE MAY BE USED IN WET AREAS (WALLS ONLY) WHEN SEALED CORRECTLY. TWO COATS OF PENETRATING SEALER ARE RECOMMENDED.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## ORIGAMI BUROKKU ZEBRA (P) *Stone, Marble*



PART NUMBER  
MB1777-BURO00

AVAILABILITY  
IN STOCK

DIMENSIONS  
8.12" x 7.10" = .297 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when sealed properly	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# HOSHI THASSOS (P) *Stone, Marble*



PART NUMBER  
**MB1232-HOSH00**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**10.15" x 11.75" = .828 sqft**

THICKNESS  
**3/8"**

PROFILE  
**MOSAIC**

VARIATION  
**LOW**

GROUT JOINT  
**1/16"**

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## HOSHI DOLOMITE (H) *Stone, Marble*



PART NUMBER  
MB1796-HOSHHO

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15 x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
LOW

GROUT JOINT  
1/8"

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# HOSHI CALACATTA (H) *Stone, Marble*



PART NUMBER  
MB1203-HOSHHO

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15" x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
HIGH

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

HOSHI WHITE HAZE (P) *Stone, Marble*



PART NUMBER	PROFILE
MB1741-HOSH00	MOSAICS
AVAILABILITY	GROUT JOINT
IN STOCK	1/16"
DIMENSIONS	SEALER
10.15" x 11.75" = .828 sqft	YES
THICKNESS	
3/8"	

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

For detailed installation instructions, visit [akdo.com](http://akdo.com).



# HOSHI CARRARA BELLA (H) *Stone, Marble*



PART NUMBER  
MB1604-HOSHHO

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15" x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
MEDIUM

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ORIGAMI HOSHI ASH GRAY (P) *Stone, Marble*



PART NUMBER  
MB1809-HOSH00

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15" x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
MEDIUM

GROUT JOINT  
1/16"

SEALER  
YES

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when properly sealed	No	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# HOSHI CARRARA (H) *Stone, Marble*



PART NUMBER  
MB1130-HOSHHO

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15" x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
MEDIUM

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

---

## ORIGAMI HOSHI ZEBRA (P) *Stone, Marble*



PART NUMBER  
MB1777-HOSH00

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15" x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when sealed properly	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

**HOSHI WHITE SAND (H)** *Limestone, Stone*



PART NUMBER	PROFILE
LS1135-HOSHHO	MOSAIC
AVAILABILITY	VARIATION
IN STOCK	MEDIUM
DIMENSIONS	GROUT JOINT
10.15" x 11.75" = .828 sqft	1/8"
THICKNESS	
3/8"	

**ENVIRONMENTS**

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	No	No	

**TECHNICAL DATA**

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## ORIGAMI HOSHI CREAM TAUPE (P) *Stone, Marble*



PART NUMBER  
MB1716-HOSH00

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15" x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
MEDIUM

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	<small>Recommended for wet areas walls only, if sealed properly.</small>	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	standard commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT. CREAM TAUPE MAY BE USED IN WET AREAS (WALLS ONLY) WHEN SEALED CORRECTLY. TWO COATS OF PENETRATING SEALER ARE RECOMMENDED.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# HOSHI OMBRA (H) *Stone, Marble*



PART NUMBER  
MB2426-HOSHHO

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15" x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
HIGH

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

---

## HOSHI TURKISH GRAY (H) *Stone, Marble*



PART NUMBER  
MB1266-HOSHHO

AVAILABILITY  
IN STOCK

DIMENSIONS  
10.15" x 11.75" = .828 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
HIGH

GROUT JOINT  
1/16"

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).



---

## ORIGAMI MASSUGU ASH GRAY (P) W/ TIGER SKIN (P)

Stone, Marble / Ash Gray (P) with Tiger Skin (P)



PART NUMBER  
MB1809-MASS00

AVAILABILITY  
IN STOCK

DIMENSIONS  
1 box = 2.2 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
MEDIUM

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when properly sealed	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

ORIGAMI MASSUGU WHITE HAZE (P) W/ DARK OLIVE (P) *Stone, Marble*



PART NUMBER  
MB1741-MASS00

AVAILABILITY  
IN STOCK

DIMENSIONS  
1 box = 2.2 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

GROUT JOINT  
1/16"

SEALER  
YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ORIGAMI MASSUGU CREAM TAUPE (P) W/ COCOA TAUPE (P)

Stone, Marble / Cream Taupe (P) with Cocoa Taupe (P)



PART NUMBER  
MB1716-MASS00

AVAILABILITY  
IN STOCK

DIMENSIONS  
1 box = 2.2 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
MEDIUM

GROUT JOINT  
1/16"

SEALER  
YES

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	<small>Recommended for wet areas walls only, if sealed properly.</small>	No	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	standard commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT. CREAM TAUPE MAY BE USED IN WET AREAS (WALLS ONLY) WHEN SEALED CORRECTLY. TWO COATS OF PENETRATING SEALER ARE RECOMMENDED.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

---

# ORIGAMI MASSUGU ZEBRA (P) W/ TULIP BLACK (P)

Stone, Marble / Zebra (P) with Tulip Black (P)



PART NUMBER  
MB1777-MASS00

AVAILABILITY  
IN STOCK

DIMENSIONS  
1 box = 2.2 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/16"

SEALER  
YES

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when sealed properly	No	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# NAMI THASSOS (P) *Stone, Marble*



PART NUMBER  
MB1232-NAMI00

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
LOW

GROUT JOINT  
1/16"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# NAMI DOLOMITE (H) *Stone, Marble*



PART NUMBER  
MB1796-NAMIH0

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
LOW

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# NAMI CALACATTA (H) *Stone, Marble*



PART NUMBER  
MB1203-NAMIH0

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
HIGH

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# NAMI WHITE HAZE (P) *Stone, Marble*



PART NUMBER  
MB1741-NAMI00

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

GROUT JOINT  
1/16"

SEALER  
YES

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes	No	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

For detailed installation instructions, visit [akdo.com](http://akdo.com).



# NAMI CARRARA BELLA (H) *Stone, Marble*



PART NUMBER  
MB1604-NAMIHO

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
MEDIUM

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ORIGAMI NAMI ASH GRAY (P) *Stone, Marble*



PART NUMBER  
MB1809-NAMI00

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
MEDIUM

GROUT JOINT  
1/16"

SEALER  
YES

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when properly sealed	No	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

**NAMI CARRARA (H)** *Stone, Marble*



PART NUMBER  
**MB1130-NAMIHO**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**9.88" x 12" = .825 sqft**

THICKNESS  
**3/8"**

PROFILE  
**MOSAIC**

VARIATION  
**MEDIUM**

GROUT JOINT  
**1/8"**

**ENVIRONMENTS**

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

**TECHNICAL DATA**

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## ORIGAMI NAMI ZEBRA (P) *Stone, Marble*



PART NUMBER  
MB1777-NAMI00

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when sealed properly	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# NAMI WHITE SAND (H) *Stone, Limestone*



PART NUMBER  
LS1135-NAMIHO

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
MEDIUM

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	No	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# NAMI OMBRA (H) *Stone, Marble*



PART NUMBER  
MB2426-NAMIH0

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAIC

VARIATION  
HIGH

GROUT JOINT  
1/8"

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## NAMI TURKISH GRAY (H) *Stone, Marble*



PART NUMBER  
MB1266-NAMIH0

AVAILABILITY  
IN STOCK

DIMENSIONS  
9.88" x 12" = .825 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
HIGH

GROUT JOINT  
1/16"

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## ORIGAMI KIKI ASH GRAY (P) *Stone, Marble*



PART NUMBER  
MB1809-KIKI00

AVAILABILITY  
IN STOCK

DIMENSIONS  
7.88" x 10.16" = .555 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
MEDIUM

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when properly sealed	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).



## ORIGAMI KIKI ZEBRA (P) *Stone, Marble*



PART NUMBER  
MB1777-KIKI00

AVAILABILITY  
IN STOCK

DIMENSIONS  
7.88" x 10.16" = .555 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when sealed properly	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## ORIGAMI LARGE SETSUMI ZEBRA (P) *Stone, Marble*



PART NUMBER  
MB1777-SESU01

AVAILABILITY  
IN STOCK

DIMENSIONS  
6.63" x 7.63" = .351 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when sealed properly	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

---

## ORIGAMI SETSUMI ZEBRA (P) *Stone, Marble*



PART NUMBER  
MB1777-SESU00

AVAILABILITY  
IN STOCK

DIMENSIONS  
7.88" x 10.2" = .555 sqft

THICKNESS  
3/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/16"

SEALER  
YES

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when sealed properly	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit [akdo.com](http://akdo.com).