

# statements | TILE & STONE

## Prestigio Onyx

Porcelain Tile

Thickness: 9mm

# of Faces: 24x24 - 26 Faces

|  | ASTM Test | ISO Test     | Specifications             |
|--|-----------|--------------|----------------------------|
| Water Absorption                       | C373      | ISO-10545/3  | ≤ 0.2%                     |
| Break Strength                         | C648      | ISO-10545/4  | Compliant                  |
| Frost Resistance                       | C1026     | ISO-10545/12 | Resistant                  |
| Stain Resistance                       | C1378     | ISO-10545/14 | Class 5                    |
| Fire Rating                            | E84       | ISO-13501/1  | Non-combustable            |
| Deep Abrasion-Unglazed Tiles           | C1243     | ISO-10545/6  | Compliant                  |
| PEI-Abrasion Resistance of Glazed Tile | C1027     | ISO-10545/7  | 5 (White, Grey); 4 (Beige) |
| Dynamic Coefficient of Friction (DCOF) | A137.1    | -            | > 0.40 (soft only)         |
| Shade and Texture Rating               | CTDA "V"  | -            | V2                         |
| Facial Dimensions                      | C499      | ISO-10545/2  | Pass                       |
| Range of Thickness                     | C499      | ISO-10545/2  | Pass                       |
| Warpage/Surface Flatness               | C485      | ISO-10545/2  | Pass                       |
| Wedging/Rectangularity                 | C502      | ISO-10545/2  | Pass                       |

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188