

## LOOM ARCTIC WHITE (C&F) *Glass*



PART NUMBER  
GL1512-LOOMCF

AVAILABILITY  
IN STOCK

DIMENSIONS  
11.75" x 11.75" = .96 sqft (+/-)

THICKNESS  
1/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/8"

SEALER  
NOT REQUIRED FOR GLASS PRODUCTS, GROUT MAY REQUIRE SEALING

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	Yes	Yes	Yes	Yes	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	<0.13%	UNE-ENISO-10545-3
Chemical resistance	Resistant	UNE-ENISO-10545-13

DUE TO THE INHERENT CHARACTERISTICS OF GLASS THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# IKAT ARCTIC WHITE (C&F) *Glass*



PART NUMBER  
GL1512-IKATCF

AVAILABILITY  
IN STOCK

DIMENSIONS  
11.25" x 9" = .706 sqft (+/-)

THICKNESS  
1/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/8"

SEALER  
NOT REQUIRED FOR GLASS PRODUCTS, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	<0.13%	UNE-ENHSO-10545-3
Chemical resistance	Resistant	UNE-ENHSO-10545-13

DUE TO THE INHERENT CHARACTERISTICS OF GLASS THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# TWILL ARCTIC WHITE (C) *Glass*



PART NUMBER  
**GL1512-TWLLC0**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**11.25" x 10.56" = .825 sqft (+/-)**

THICKNESS  
**1/8"**

PROFILE  
**MOSAICS**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
NOT REQUIRED FOR GLASS PRODUCTS, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	<0.13%	UNE-ENHSO-10545-3
Chemical resistance	Resistant	UNE-ENHSO-10545-13

DUE TO THE INHERENT CHARACTERISTICS OF GLASS THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# LOOM LUNAR GRAY MEDIUM (C&F) *Glass*



PART NUMBER  
GL1515-LOOMCF

AVAILABILITY  
IN STOCK

DIMENSIONS  
11.75" x 11.75" = .96 sqft (+/-)

THICKNESS  
1/8"

PROFILE  
MOSAICS

VARIATION  
LOW

GROUT JOINT  
1/8"

SEALER  
NOT REQUIRED FOR GLASS PRODUCTS, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	<0.13%	UNE-ENISO-10545-3
Chemical resistance	Resistant	UNE-ENISO-10545-13

DUE TO THE INHERENT CHARACTERISTICS OF GLASS THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## LOOM SILVER SILK (C&F) *Glass*



PART NUMBER  
GL2102-LOOMCF

AVAILABILITY  
IN STOCK

DIMENSIONS  
11.75" x 11.75" = .96 sqft (+/-)

THICKNESS  
1/8"

PROFILE  
MOSAICS

VARIATION  
MEDIUM

GROUT JOINT  
1/8"

SEALER  
NOT REQUIRED FOR GLASS PRODUCTS, GROUT MAY REQUIRE SEALING

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	No	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	<0.13%	UNE-ENISO-10545-3
Chemical resistance	Resistant	UNE-ENISO-10545-13
Heat Resistance	Heat not to exceed 293° F	96/603/CE
TRAFFIC	Wall Only	NA

DUE TO THE INHERENT CHARACTERISTICS OF GLASS THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT. WHEN USING METALLIC GLASS IN A BACKSPASH DESIGN, INCLUDE A 4" SPLASH GUARD OF WET AREA APPROPRIATE MATERIAL IN AREAS WHERE WATER MAY POOL, SUCH AS BEHIND FAUCETS.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

---

## STRIPE LINER ARCTIC WHITE (C) *Glass*



PART NUMBER  
**GL1512-STLN01**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**.38" x 11.75" = .98 lft (+/-)**

THICKNESS  
**5/16"**

PROFILE  
**TRIM**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
NOT REQUIRED FOR GLASS PRODUCTS, GROUT MAY REQUIRE SEALING

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	Yes	Yes	Yes	Yes	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	<0.13%	UNE-ENISO-10545-3
Chemical resistance	RESISTANT	UNE-ENISO-10545-13

DUE TO THE INHERENT CHARACTERISTICS OF GLASS THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

---

## STRIPE LINER LUNAR GRAY MEDIUM (C) *Glass*



PART NUMBER  
**GL1515-STLN01**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**.38" x 11.75" = .98 lft (+/-)**

THICKNESS  
**5/16"**

PROFILE  
**TRIM**

VARIATION  
**LOW**

GROUT JOINT  
**1/16"**

SEALER  
NOT REQUIRED FOR GLASS PRODUCTS, GROUT MAY REQUIRE SEALING

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	Yes	Yes	Yes	Yes	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	<0.13%	UNE-ENHSO-10545-3
Chemical resistance	resistant	UNE-ENHSO-10545-13

DUE TO THE INHERENT CHARACTERISTICS OF GLASS THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

---

## STRIPE LINER SILVER SILK (C) *Glass*



PART NUMBER  
**GL2102-STLN01**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**.38" x 11.75" = .98 lft (+/-)**

THICKNESS  
**5/16"**

PROFILE  
**TRIM**

VARIATION  
**MEDIUM**

GROUT JOINT  
**1/16"**

SEALER  
NOT REQUIRED FOR GLASS PRODUCTS, GROUT MAY REQUIRE SEALING

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	No	No	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	<0.13%	UNE-ENISO-10545-3
Chemical resistance	RESISTANT	UNE-ENISO-10545-13
Heat Resistance	Heat not to exceed 293° F	96/603/CE
TRAFFIC	Wall Only	NA

DUE TO THE INHERENT CHARACTERISTICS OF GLASS THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT. WHEN USING METALLIC GLASS IN A BACKSPASH DESIGN, INCLUDE A 4" SPLASH GUARD OF WET AREA APPROPRIATE MATERIAL IN AREAS WHERE WATER MAY POOL, SUCH AS BEHIND FAUCETS.

For detailed installation instructions, visit [akdo.com](http://akdo.com).