

statements | TILE & STONE

WOW Abbey Stone

Porcelain Tile

Thickness: 10mm

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≤ 0.5%
Break Strength	C648	ISO-10545/4	Minimum 35 N/mm ²
Chemical Resistance	C650	ISO-10545/13	GA
Crazing Resistance	C424	ISO-10545/11	Pass
Frost Resistance	C1026	ISO-10545/12	Pass
Stain Resistance	C1378	ISO-10545/14	5
Fire Rating	E84	ISO-13501/1	Non-Combustible
PEI-Abrasion Resistance of Glazed Tile	C1027	ISO-10545/7	PEI 4 (Sintra) PEI 3 (Rila & Cluny)
Dynamic Coefficient of Friction (DCOF)	A137.1	-	R11 / DCOF >0.42
Shade and Texture Rating	CTDA "V"	-	V5
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188