

LUSTER 4" X 12" OYSTER (PEARL) *Ceramic*



PART NUMBER
CR2410-0412PO

AVAILABILITY
IN STOCK

DIMENSIONS
3.94" x 11.81" = .323 sqft

THICKNESS
3/8"

PROFILE
TILE

GROUT JOINT
1/8"

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Stain resistance	Class 5	UNE-ENISO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.

LUSTER MINIMALIST LINER OYSTER (PEARL) *Ceramic*



PART NUMBER
CR2410-LN12PO

AVAILABILITY
IN STOCK

DIMENSIONS
.51" x 11.81" = .98 lmf

THICKNESS
3/8"

PROFILE
TRIM

GROUT JOINT
1/8"

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Stain resistance	Class 5	UNE-ENISO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.

LUSTER MINIMALIST CORNER OYSTER (PEARL) *Ceramic*



PART NUMBER
CR2410-LNCRPO

PROFILE
TRIM

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

THICKNESS
3/8"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Stain resistance	Class 5	UNE-ENISO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.

LUSTER 4" X 12" SEAL GRAY (PEARL) *Ceramic*



PART NUMBER
CR2409-0412PO

AVAILABILITY
IN STOCK

DIMENSIONS
3.94" x 11.81" = .323 sqft

THICKNESS
3/8"

PROFILE
TILE

GROUT JOINT
1/8"

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Stain resistance	Class 5	UNE-ENISO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.

LUSTER MINIMALIST LINER SEAL GRAY (PEARL) *Ceramic*



PART NUMBER
CR2409-LN12P0

AVAILABILITY
IN STOCK

DIMENSIONS
.51" x 11.81" = .98 lmf

THICKNESS
3/8"

PROFILE
TRIM

GROUT JOINT
1/8"

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Stain resistance	Class 5	UNE-ENISO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.

LUSTER MINIMALIST CORNER SEAL GRAY (PEARL) *Ceramic*

PART NUMBER
CR2409-LNCRPO

PROFILE
TRIM

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
.042" X .042" = .001

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

THICKNESS
3/8"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Stain resistance	Class 5	UNE-ENISO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.

LUSTER 4" X 12" COASTAL (PEARL) *Ceramic*



PART NUMBER
CR2411-0412PO

AVAILABILITY
IN STOCK

DIMENSIONS
3.94" x 11.81" = .323 sqft

THICKNESS
3/8"

PROFILE
TILE

GROUT JOINT
1/8"

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Stain resistance	Class 5	UNE-ENISO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.

LUSTER MINIMALIST LINER COASTAL (PEARL) *Ceramic*



PART NUMBER
CR2411-LN12P0

AVAILABILITY
IN STOCK

DIMENSIONS
.51" x 11.81" = .98 lnt

THICKNESS
3/8"

PROFILE
TRIM

GROUT JOINT
1/8"

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENHSO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENHSO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENHSO-10545-9
Crazing resistance	Resistant	UNE-ENHSO-10545-11
Stain resistance	Class 5	UNE-ENHSO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.

LUSTER MINIMALIST CORNER COASTAL (PEARL) *Ceramic*



PART NUMBER
CR2411-LNCRPO

PROFILE
TRIM

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS

SEALER
NOT REQUIRED, GROUT MAY REQUIRE SEALING

THICKNESS
3/8"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	Yes	Yes	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	Compliant	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	Compliant	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Stain resistance	Class 5	UNE-ENISO-10545-14
TRAFFIC	Wall Only	NA

For detailed installation instructions, visit akdo.com.