

statements | TILE & STONE

WOW Tesserae

Porcelain Tile

Thickness: 8.5mm

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	<= 0,5%
Break Strength	C648	ISO-10545/4	Minimum 35 N/mm ²
Chemical Resistance	C650	ISO-10545/13	GHA
Crazing Resistance	C424	ISO-10545/11	Pass
Frost Resistance	C1026	ISO-10545/12	Pass
Stain Resistance	C1378	ISO-10545/14	5
Fire Rating	E84	ISO-13501/1	Non-Combustable
PEI-Abrasion Resistance of Glazed Tile	C1027	ISO-10545/7	4: Blanc, Grana, Marino 3: Grana Plus, Marino Plus
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>0,42 ; R10
Shade and Texture Rating	CTDA "V"	-	V3
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188