

POSE FINO CALACATTA (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1203-FINOHO MOSAIC IN STOCK

DIMENSIONS

7.87" x 9.29" =0.508 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes

FIREPLACE SURROUND

Yes



POSE FINO DOLOMITE (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY MB1796-FINOHO MOSAIC IN STOCK

GROUT JOINT DIMENSIONS THICKNESS 1/8" 3/8"

 $7.87" \times 9.29" = 0.508 \text{ sqft}$

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

It is important to properly seal marble used in a shower/steam shower, and maintain the sealant regularly to ensure water beads off the tile.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	YES - when properly sealed	YES - when properly sealed	No	Yes

FIREPLACE SURROUND

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION

DCOF - ANSI A. 137. 1



POSE FINO LILAC (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1053-FINOHO MOSAIC IN STOCK

GROUT JOINT DIMENSIONS THICKNESS

1/8" 7.87" x 9.29" =0.508 sqft 3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	Yes	Yes - If Properly Sealed	Yes - If Properly Sealed	No	Yes
FIREPLACI		KITCHEN FLOOR					
Yes		No					

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

DCOF - ANSI A.137.1

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION

akdo.com



POSE FINO MOSS GREEN (H)

Stone, Marble



PART NUMBER PROFILE AVAILABILITY
MB1088-FINOHO MOSAIC IN STOCK

GROUT JOINT DIMENSIONS THICKNESS

1/8" 7.87" x 9.29" = 0.508 sqft

NOTES

 $\label{eq:decomposition} \mbox{Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.}$

For wet applications, such as showers and steam showers, moss green marble must be installed with an epoxy adhesive and grout. please contact your akdo sales representative for specific recommendations.

3/8"

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Light Commercial	Yes	Yes - If Properly Sealed	Yes - If Properly Sealed	No	Yes

FIREPLACE SURROUND

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION

DCOF - ANSI A. 137.1



POSE FINO ASH GRAY (COMBED) Stone, Marble



PART NUMBER PROFILE AVAILABILITY
MB1809-FINO01 MOSAIC IN STOCK

DIMENSIONS

7.87" x 9.29" =0.508 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes

FIREPLACE SURROUND

Yes



POSE FINO THASSOS (COMBED) Stone, Marble



PART NUMBER PROFILE
MB1232-FINO01 MOSAIC

DIMENSIONS

 $7.87" \times 9.29" = 0.508 \text{ sqft}$

AVAILABILITY IN STOCK

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes

FIREPLACE SURROUND

Yes



POSE FINO TULIP BLACK (COMBED) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1187-FINO01 MOSAIC IN STOCK

DIMENSIONS

 $7.87" \times 9.29" = 0.508 \text{ sqft}$

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes

FIREPLACE SURROUND

Yes



POSE POLI CALACATTA (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY
MB1203-POLIHO MOSAIC IN STOCK

DIMENSIONS 11.14" x 12.56" =0.925 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes

FIREPLACE SURROUND

Yes

AKDO

POSE POLI DOLOMITE (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1796-POLIHO MOSAIC IN STOCK

GROUT JOINT DIMENSIONS THICKNESS

1/8" 11.10" x 12" =0.925 sqft 3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

It is important to properly seal marble used in a shower/steam shower, and maintain the sealant regularly to ensure water beads off the tile.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	YES - when properly sealed	YES - when properly sealed	No	Yes

FIREPLACE SURROUND

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

TECHNICAL DATA			
FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
DCOF - ANSI A.137.1			

AKDO

POSE POLI LILAC (H) Stone, Marble



1/8"	$11.10" \times 12" = 0.925 \text{ sqft}$	3/8"
GROUT JOINT	DIMENSIONS	THICKNESS
MB1053-POLIH0	MOSAIC	IN STOCK
PART NUMBER	PROFILE	AVAILABILITY

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	Yes	Yes - If Properly Sealed	Yes - If Properly Sealed	No	Yes

FIREPLACE SURROUND

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
DCOF - ANSI A.137.1			



POSE POLI MOSS GREEN (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY
MB1088-POLIHO MOSAIC IN STOCK

GROUT JOINT DIMENSIONS THICKNESS 1/8" 11.10" x 12" =0.925 sqft 3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

For wet applications, such as showers and steam showers, moss green marble must be installed with an epoxy adhesive and grout. please contact your akdo sales representative for specific recommendations.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Light Commercial	Yes	Yes - If Properly Sealed	Yes - If Properly Sealed	No	Yes

FIREPLACE SURROUND

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installar for more information.

TECHNICAL DATA

DCOF - ANSI A. 137. 1

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION



POSE POLI ASH GRAY (COMBED) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1809-POLI01 MOSAIC IN STOCK

DIMENSIONS 11.14" x 12.56" =0.925 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes

FIREPLACE SURROUND

Yes



POSE POLI THASSOS (COMBED) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1232-POLI01 MOSAIC IN STOCK

DIMENSIONS 11.14" x 12.56" =0.925 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes

FIREPLACE SURROUND

Yes



POSE POLI TULIP BLACK (COMBED) Stone, Marble



PART NUMBER PROFILE MB1187-POLI01

MOSAIC

AVAILABILITY IN STOCK

DIMENSIONS

 $11.14" \times 12.56" = 0.925 \text{ sqft}$

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes

FIREPLACE SURROUND



POSE PLIA CALACATTA (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1203-PLIAHO MOSAIC IN STOCK

DIMENSIONS

11.14" x 12.56" =0.972 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes
FIDEDI A							

FIREPLACE SURROUND

Yes

AKDO

POSE PLIA DOLOMITE (H) Stone, Marble



PART NUMBER	PROFILE	AVAILABILITY
MB1796-PLIAHO	MOSAIC	IN STOCK
GROUT JOINT	DIMENSIONS	THICKNESS
1/8"	11.14" x 12.56" =0.972 sqft	3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM	WET	POOL	BACKSPLASH	
			FREEZE/THAW	SHOWER	AREA			
Yes	Yes	Standard	No	YES - when properly	YES - when properly	No	Yes	
		Commercial		sealed	sealed			
FIREPLAC	CE	KITCHEN						
SURROU	IND	FLOOR						
Yes		No						
165		170						

тг	\sim I	IK I	1 A	IГ	\ A T	Α
11	(.F	V	ICA	ш)AI	А

TECHNICALDAIA			
FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
DCOF - ANSLA 137 1			



POSE PLIA MOSS GREEN (H) Stone, Marble



PART NUMBER PROFILE AVAILABILITY MB1088-PLIAHO MOSAIC IN STOCK

GROUT JOINT DIMENSIONS THICKNESS 1/8" 3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

For wet applications, such as showers and steam showers, moss green marble must be installed with an epoxy adhesive and grout. please contact your akdo sales representative for specific recommendations.

 $11.14" \times 12.56" = 0.972$ sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Light Commercial	Yes	Yes - If Properly Sealed	Yes - If Properly Sealed	No	Yes

FIREPLACE SURROUND

Yes

TECHNICAL DATA			
FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
DCOF - ANSI A. 137.1			



POSE PLIA TULIP BLACK (H&P)

Stone, Marble



PART NUMBER PROFILE AVAILABILITY
MB1187-PLIA00 MOSAIC IN STOCK

GROUT JOINT DIMENSIONS THICKNESS

3/8"

1/8" 11.14" x 12.56" =0.972 sqft

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	YES - when properly sealed	YES - when properly sealed	No	Yes

FIREPLACE SURROUND

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

DCOF - ANSI A. 137.1

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION

akdo.com



POSE PLIA TURKISH GRAY TEXT (SB) Stone, Marble



PART NUMBER PROFILE AVAILABILITY

MB1266-PLIATS MOSAIC IN STOCK

DIMENSIONS 11.14" x 12.56" =0.972 sqft

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Standard Commercial	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes
FIDEDI A	`_						

FIREPLACE SURROUND

Yes