

3" X 9" TURKISH GRAY (H) *Stone, Marble*



PART NUMBER
MB1266-0309H0

AVAILABILITY
IN STOCK

DIMENSIONS
2.95" x 9" = .18 sqft (+/-)

THICKNESS
3/8"

PROFILE
TILE

VARIATION
HIGH

GROUT JOINT
1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

4" X 12" TURKISH GRAY (H) *Stone, Marble*

	PART NUMBER	PROFILE
	MB1266-0412H0	TILES
	AVAILABILITY	VARIATION
	IN STOCK	MEDIUM
	DIMENSIONS	GROUT JOINT
	4" x 12" = .333 sqft (+/-)	1/8"
	THICKNESS	SEALER
	3/8"	YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	No	Yes - if sealed properly	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

12" X 24" TURKISH GRAY (H) *Marble, Stone*



PART NUMBER	PROFILE
MB1266-1224H1	TILES
AVAILABILITY	GROUT JOINT
IN STOCK	1/16"
DIMENSIONS	SEALER
12" x 24" = 2 sqft (+/-)	YES
THICKNESS	
3/8"	

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	No	Yes - if sealed properly	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

HEXAGON 3-7/8 TURKISH GRAY (H)

Stone, Marble



PART NUMBER
MB1266-HEX3H0

AVAILABILITY
IN STOCK

DIMENSIONS
7.88" x 10.25" = .56 sqft

THICKNESS
3/8"

PROFILE
MOSAICS

VARIATION
HIGH

GROUT JOINT
1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

HEXAGON TURKISH GRAY (H) *Stone, Marble*



PART NUMBER
MB1266-HEXAH0

AVAILABILITY
IN STOCK

DIMENSIONS
9.75" x 10.13" = .69 sqft

THICKNESS
3/8"

PROFILE
MOSAICS

VARIATION
MEDIUM

GROUT JOINT
1/8"

SEALER
YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	No	Yes - if sealed properly	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

1" X 4" HERRINGBONE TURKISH GRAY (H) *Stone, Marble*



PART NUMBER
MB1266-HB14H0

AVAILABILITY
IN STOCK

DIMENSIONS
9" x 11.5" = .72 sqft

THICKNESS
3/8"

PROFILE
MOSAICS

VARIATION
MEDIUM

GROUT JOINT
1/8"

SEALER
YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	No	Yes - if sealed properly	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

BASKET WEAVE TURKISH GRAY (H) W/ CARRARA (H)

Stone, Marble / Turkish Gray (H) & Carrara (H) Dots Interlocking



PART NUMBER
MB1266-BASIHO

AVAILABILITY
IN STOCK

DIMENSIONS
9.75" x 9.75" = .66 sqft

THICKNESS
5/16"

PROFILE
MOSAICS

VARIATION
MEDIUM

GROUT JOINT
1/16"

SEALER
YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes	Yes, when sealed properly	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

2" X 4" BRICK TURKISH GRAY (H) *Stone, Marble*



PART NUMBER
MB1266-BRICH0

AVAILABILITY
IN STOCK

DIMENSIONS
9.75" x 11.75" = .8 sqft

THICKNESS
3/8"

PROFILE
MOSAICS

VARIATION
MEDIUM

GROUT JOINT
1/8"

SEALER
YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	No	Yes - if sealed properly	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

IVY TURKISH GRAY (H&P) *Stone, Marble*



PART NUMBER
MB1266-IVY000

AVAILABILITY
IN STOCK

DIMENSIONS
9.88" x 11.75" = .814 sqft

THICKNESS
3/8"

PROFILE
MOSAICS

VARIATION
HIGH

GROUT JOINT
1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

HOSHI TURKISH GRAY (H)

Stone, Marble



PART NUMBER	PROFILE
MB1266-HOSHHO	MOSAICS
AVAILABILITY	VARIATION
IN STOCK	HIGH
DIMENSIONS	GROUT JOINT
10.15" x 11.75" = .828 sqft	1/16"
THICKNESS	
3/8"	

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

NAMI TURKISH GRAY (H) *Stone, Marble*



PART NUMBER
MB1266-NAMIHO

AVAILABILITY
IN STOCK

DIMENSIONS
9.88" x 12" = .825 sqft

THICKNESS
3/8"

PROFILE
MOSAICS

VARIATION
HIGH

GROUT JOINT
1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	Yes when properly sealed	Yes when properly sealed	No	

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

12" CLASSIC RAIL TURKISH GRAY (H) *Stone, Marble*



PART NUMBER
MB1266-RM12H0

AVAILABILITY
IN STOCK

DIMENSIONS
1 lft (+/-)

THICKNESS
7/8"

PROFILE
TRIM

VARIATION
MEDIUM

SEALER
YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes		Yes	Yes	No	Yes - if sealed properly	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

12" NARROW LINER TURKISH GRAY (H) *Stone, Marble*



PART NUMBER
MB1266-NL12H0

AVAILABILITY
IN STOCK

DIMENSIONS
1 lft (+/-)

THICKNESS
13/16"

PROFILE
TRIM

VARIATION
MEDIUM

SEALER
YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes		Yes	Yes	No	Yes - if sealed properly	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
DCOF		ANSI A137.1
TRAFFIC	Standard Commercial	NA

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

MICRO PITS OR SCRATCHES MAY APPEAR WHITE, THEREFORE USING A COMPLIMENTARY GRAY GROUT IS RECOMMENDED.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

For detailed installation instructions, visit akdo.com.

