

# ARCADIA GRAIN BEECH (M) *Porcelain*



PART NUMBER  
**PO2384-GRA100**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**3.86" x 18.31" = .491 sqft**

THICKNESS  
**3/8"**

PROFILE  
**TILES**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
**NOT REQUIRED, GROUT MAY REQUIRE SEALING**

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	□ 0.5%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	>35 N/ mm <sup>2</sup>	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Frost resistance	Resistant	UNE-ENISO-10545-12
Chemical resistance	ISO 10545-13 GLA	UNE-ENISO-10545-13
Stain resistance	5	UNE-ENISO-10545-14
DCOF	□ 0.47	ANSI A137.1
Heat Resistance	A1-A1FL 96/603/CE	96/603/CE
TRAFFIC	Moderate Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ARCADIA GRAIN OAK (M) *Porcelain*



PART NUMBER  
PO2382-GRA100

AVAILABILITY  
IN STOCK

DIMENSIONS  
3.86" x 18.31" = .491 sqft

THICKNESS  
3/8"

PROFILE  
TILES, PLANKS

VARIATION  
LOW

GROUT JOINT  
1/8"

SEALER  
NOT REQUIRED, GROUT MAY REQUIRE SEALING

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	□ 0.5%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	>35 N/ mm <sup>2</sup>	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Frost resistance	Resistant	UNE-ENISO-10545-12
Chemical resistance	ISO 10545-13 GLA	UNE-ENISO-10545-13
Stain resistance	5	UNE-ENISO-10545-14
DCOF	□ 0.47	ANSI A137.1
Heat Resistance	A1-A1FL 96/603/CE	96/603/CE
TRAFFIC	Light Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ARCADIA GRAIN SILVER PINE (M) *Porcelain*



PART NUMBER  
**PO2381-GRA100**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**3.94" x 18.62" = .491 sqft**

THICKNESS  
**3/8"**

PROFILE  
**TILES**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
**NOT REQUIRED, GROUT MAY REQUIRE SEALING**

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	□ 0.5%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	>35 N/ mm <sup>2</sup>	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Frost resistance	Resistant	UNE-ENISO-10545-12
Chemical resistance	ISO 10545-13 GLA	UNE-ENISO-10545-13
Stain resistance	5	UNE-ENISO-10545-14
DCOF	□ 0.47	ANSI A137.1
Heat Resistance	A1-A1FL 96/603/CE	96/603/CE
TRAFFIC	Light Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ARCADIA GRAIN EBONY (M) *Porcelain*



PART NUMBER  
**PO2383-GRA100**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**3.86" x 18.31" = .491 sqft**

THICKNESS  
**3/8"**

PROFILE  
**TILES, PLANKS**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
**NOT REQUIRED, GROUT MAY REQUIRE SEALING**

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	□ 0.5%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	>35 N/ mm <sup>2</sup>	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Frost resistance	Resistant	UNE-ENISO-10545-12
Chemical resistance	ISO 10545-13 GLA	UNE-ENISO-10545-13
Stain resistance	5	UNE-ENISO-10545-14
DCOF	□ 0.47	ANSI A137.1
Heat Resistance	A1-A1FL 96/603/CE	96/603/CE
TRAFFIC	Residential	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

## ARCADIA MILL OAK (M) *Porcelain*



PART NUMBER  
**PO2382-MILL00**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**7.28" x 7.28" = .368 sqft**

THICKNESS  
**3/8"**

PROFILE  
**TILES**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
**NOT REQUIRED, GROUT MAY REQUIRE SEALING**

### ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

### TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	□ 0.5%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	>35 N/ mm <sup>2</sup>	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Frost resistance	Resistant	UNE-ENISO-10545-12
Chemical resistance	ISO 10545-13 GLA	UNE-ENISO-10545-13
Stain resistance	5	UNE-ENISO-10545-14
DCOF	□ 0.47	ANSI A137.1
Heat Resistance	A1-A1FL 96/603/CE	96/603/CE
TRAFFIC	Light Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ARCADIA MILL SILVER PINE (M) *Porcelain*



PART NUMBER  
**PO2381-MILL00**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**7.28" x 7.28" = .368 sqft**

THICKNESS  
**3/8"**

PROFILE  
**TILES**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
**NOT REQUIRED, GROUT MAY REQUIRE SEALING**

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	□ 0.5%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	>35 N/ mm <sup>2</sup>	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Frost resistance	Resistant	UNE-ENISO-10545-12
Chemical resistance	ISO 10545-13 GLA	UNE-ENISO-10545-13
Stain resistance	5	UNE-ENISO-10545-14
DCOF	□ 0.47	ANSI A137.1
Heat Resistance	A1-A1FL 96/603/CE	96/603/CE
TRAFFIC	Light Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ARCADIA HEARTWOOD OAK (M) *Porcelain*



PART NUMBER  
**PO2382-HRTW00**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**5.28" equilateral = .494 sqft**

THICKNESS  
**3/8"**

PROFILE  
**TILES**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
**NOT REQUIRED, GROUT MAY REQUIRE SEALING**

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	□ 0.5%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	>35 N/ mm <sup>2</sup>	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Frost resistance	Resistant	UNE-ENISO-10545-12
Chemical resistance	ISO 10545-13 GLA	UNE-ENISO-10545-13
Stain resistance	5	UNE-ENISO-10545-14
DCOF	□ 0.47	ANSI A137.1
Heat Resistance	A1-A1FL 96/603/CE	96/603/CE
TRAFFIC	Light Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).

# ARCADIA HEARTWOOD SILVER PINE (M) *Porcelain*



PART NUMBER  
**PO2381-HRTW00**

AVAILABILITY  
**IN STOCK**

DIMENSIONS  
**5.28" equilateral = .494 sqft**

THICKNESS  
**3/8"**

PROFILE  
**TILES**

VARIATION  
**LOW**

GROUT JOINT  
**1/8"**

SEALER  
**NOT REQUIRED, GROUT MAY REQUIRE SEALING**

## ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	Yes	Yes	Yes	Yes	No

## TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Water absorption	□ 0.5%	UNE-ENISO-10545-3
Modulus of rupture and breaking strength	>35 N/ mm <sup>2</sup>	UNE-ENISO-10545-4
Thermal Shock Resistance	Resistant	UNE-ENISO-10545-9
Crazing resistance	Resistant	UNE-ENISO-10545-11
Frost resistance	Resistant	UNE-ENISO-10545-12
Chemical resistance	ISO 10545-13 GLA	UNE-ENISO-10545-13
Stain resistance	5	UNE-ENISO-10545-14
DCOF	□ 0.47	ANSI A137.1
Heat Resistance	A1-A1FL 96/603/CE	96/603/CE
TRAFFIC	Light Commercial	NA

AVAILABLE NATIONWIDE.

DUE TO THE INHERENT CHARACTERISTICS OF PORCELAIN, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

For detailed installation instructions, visit [akdo.com](http://akdo.com).