



Abaco



Abaco

Innovative, versatile and extremely functional, the Abaco collection takes the nuances of concrete to their highest expression, improving them with the durability of porcelain tile.

Abaco Grafito 24"x24" R

Color Body Porcelain

12"x24" R - 24"x48" R



Abaco In&Out Arena 24"x48" R



Abaco In&Out Grafito 24"x48" R



Abaco Oxido


IN&OUT



The first soft slip resistant floor tile

The In&Out finish is the result of Roca Tile's commitment to R&D. The innovative manufacturing process developed for In&Out, provides a silky, and at the same time, slip resistant surface, reaching the maximum values required by the Class 3 Technical Building Code for exteriors.

Abaco Arena In&Out 24"x48" R



12"x24"
30x60cm

24"x48"
60x120cm



Gris



In & Out 24"x48" R
FWMRA54021



12"x24" R
FWMR057021



Arena



In & Out 24"x48" R
FWMRA54371



12"x24" R
FWMR057371



Grafito



In & Out 24"x48" R
FWMRA54101



12"x24" R
FWMR057101



Oxido



In & Out 24"x48" R
FWMRA54961



12"x24" R
FWMR057961

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM	
		IN & OUT	MATTE
Water Absorption	C373	<=0.5	<=0.5
Break Strength	C648	Min. 450	Min. 450
Scratch Hardness	MOH's Scale	7	7
Chemical Resistance	C650	Unaffected	Unaffected
Frost Resistance	C1026	Resistant	Resistant
Group	See FAQ's	4	4
Deep Abrasion - Unglazed Tiles	C1243	Pass	Pass
PEI - Glazed Tiles	C1027	-	-
Minimum Bond Strength (PSI)	C482	165	165
Dynamic Coefficient of Friction (DCOF)	A1371	>=0.50	>=0.42
Shade and Texture Rating	CTDA "V"	V3	V3
Facial Dimensions	C499	Pass	Pass
Range of Thickness	C499	Pass	Pass
Warpage	C485	Pass	Pass
Wedging	C502	Pass	Pass

Packaging Info

Size	SF per carton	PC per carton
12"x24"	13.56	7
24"x48"	15.50	2