

statements | TILE & STONE

Aextra20

Porcelain Paver
 Thickness: 20mm
 # of Faces: Over 25 Faces

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≤ 0.5%
Break Strength	C648	ISO-10545/4	≥3000 lbs
Scratch Hardness	MOH's Scale	EN-101	6
Chemical Resistance	C650	ISO-10545/13	Unaffected
Crazing Resistance	C424	ISO-10545/11	Crazing Resistance
Frost Resistance	C1026	ISO-10545/12	Frost Resistance
Stain Resistance	C1378	ISO-10545/14	Stain Resistance
Fire Rating	E84	ISO-13501/1	Non-Combustable
Dynamic Coefficient of Friction (DCOF)	A137.1	-	R11
Shade and Texture Rating	CTDA "V"	-	V3-Pen Blue Only, V2-all other
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188