

statements | TILE & STONE

Calacata Gold

Porcelain

Thickness: 10mm (24x48), 8.5mm (12x24)

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	<= 0.5%
Break Strength	C648	ISO-10545/4	Min. 335
Scratch Hardness	MOH's Scale	EN-101	5-unpol. ; 3-pol.
Chemical Resistance	C650	ISO-10545/13	Unaffected
Frost Resistance	C1026	ISO-10545/12	Resistant
Fire Rating	E84	ISO-13501/1	Non-combustable
Deep Abrasion-Unglazed Tiles	C1243	ISO-10545/6	Pass
PEI-Abrasion Resistance of Glazed Tile	C1027	ISO-10545/7	4-unpol ; 3-pol.
Minimum Bond Strength (PSI)	C482	-	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>0.42 unpol. ; <0.40 pol.
Shade and Texture Rating	CTDA "V"	-	V3
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188