

# statements | TILE & STONE

## RC Classic Mondrian (reverse bevel)

Ceramic Wall Tile

Thickness: 7.5mm

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	>10%
Break Strength	C648	ISO-10545/4	Meets or Exceeds
Scratch Hardness	MOH's Scale	EN-101	N/A
Chemical Resistance	C650	ISO-10545/13	Unaffected
Shade and Texture Rating	CTDA "V"	-	V1
Warpage	C485	ISO-10545/2	Pass
Wedging	C502	ISO-10545/2	Pass

## RC Classic Bevel

Ceramic Wall Tile

Thickness: 7mm (3x6 BV)

7.3mm (4x10 BV)

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	>10%
Break Strength	C648	ISO-10545/4	Meets or Exceeds
Scratch Hardness	MOH's Scale	EN-101	3
Chemical Resistance	C650	ISO-10545/13	Unaffected
Shade and Texture Rating	CTDA "V"	-	V1
Warpage	C485	ISO-10545/2	Pass
Wedging	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188