

# statements | TILE & STONE

## Downtown

Colored Body Porcelain Tile

Thickness: 8.7mm/11 mm (32 x 32)

# of Faces: 12x24 - 22 Faces | 24x24 - 11 Faces

	ASTM Test	ISO Test	Declared ATSM
Water Absorption	C373	ISO-10545/3	<=0.1%
Break Strength	C648	ISO-10545/4	Min. 450
Scratch Hardness	MOH's Scale	EN-101	7
Chemical Resistance	C650	ISO-10545/13	Resistant
Frost Resistance	C1026	ISO-10545/12	Resistant
Deep Abrasion - Unglazed Tiles	C1243	ISO-10545/6	Passes
PEI- Abrasion Resistance of Glazed Tiles	C1027	ISO-10545/7	-
Minimum Bond Strength (PSI)	C482	-	165
Dynamic Coefficient of Friction (DCOF)	A137.1	-	>=0.42
Shade and Texture Rating	CTDA "V"	-	V3
Facial Dimensions	C499	ISO-10545/2	Passes
Range of Thickness	C499	ISO-10545/2	Passes
Warpage	C485	ISO-10545/2	Passes
Wedging	C502	ISO-10545/2	Passes

Statements Tile & Stone

6140 6th Ave S

Seattle, WA 98108