





Allegato alla Dichiarazione di Prestazione  
Attachment to Declaration of Performance  
Annexe à la déclaration de performance  
Anhang der Leistungserklärung  
Anexo a la Declaración de Performance  
Załącznik do deklaracji właściwości użytkowych  
A Teljesítmény Nyilatkozat kiegészítő táblázata  
Bijlage bij de prestatieverklaring  
Navezanost na izjave o lastnostih  
Aneks Izjave o svojstvima  
No. FLORIM 001

Tabella - Scivolosità (dove richiesto dalla legislazione)  
Table - Slipperiness (where required by regulation)  
Table - Glissement (si requis par la loi)  
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)  
Tabla - Deslizamiento (donde sea requerido por ley)  
Tabela - Poslizgowosc (gdzie wymagane przez prawo)  
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)  
Tabel - Antislipwaarde (indien door de wetgever vereist)  
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)  
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)  
Rev. 2 del/of/de/vom/de/a 17.12.2019

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

## FLORIMSTONE


Serie / Series / Kolekcja / Serija	CEN/TS 16165:2012 Annex B $\alpha_{SHOD}$	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
CEMENT velvet 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
COLOR glossy 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
MARBLE glossy 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
METAL matte 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
STONE matte 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.



FLORIM CERAMICHE S.p.A. a socio unico  
VIA CANALETTO 24 / 41042 FIORANO MODENESE (MO) ITALY  
T. +39 0536 840111 / F. +39 0536 840322  
[www.florim.com](http://www.florim.com)

# CE MARKING

Fine porcelain stoneware  
Glazed porcelain stoneware  
Coloured body porcelain stoneware

	
<b>FLORIM CERAMICHE S.p.A., Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia</b>	
05 FLORIM 001	
<b>EN 14411:2012</b> Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$ , for internal and external walls and floorings	
<b>Reaction to fire</b>	A1 <sub>FL</sub> /A1
<b>Release of dangerous substances, for:</b>	
- Cadmium	NPD
- Lead	NPD
<b>Breaking strength</b>	> 1300 N
<b>Slipperiness, as:</b>	See table attached
<b>Tactility</b>	NPD
<b>Bond strength/adhesion, for:</b>	
Cementitious adhesive, type C2	NPD
<b>Thermal shock resistance</b>	Pass
<b>Durability, for:</b>	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass





Allegato alla Dichiarazione di Prestazione  
Attachment to Declaration of Performance  
Annexe à la déclaration de performance  
Anhang der Leistungserklärung  
Anexo a la Declaración de Performance  
Załącznik do deklaracji właściwości użytkowych  
A Teljesítmény Nyilatkozat kiegészítő táblázata  
Bijlage bij de prestatieverklaring  
Navezanost na izjave o lastnostih  
Aneks Izjave o svojstvima  
No. FLORIM 003

Tabella - Scivolosità (dove richiesto dalla legislazione)  
Table - Slipperiness (where required by regulation)  
Table - Glissement (si requis par la loi)  
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)  
Tabla - Deslizamiento (donde sea requerido por ley)  
Tabela - Poslizgowosc (gdzie wymagane przez prawo)  
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)  
Tabel - Antislipwaarde (indien door de wetgever vereist)  
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)  
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)  
Rev. 8 del/of/de/vom/de/a 23.12.2019

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

## FLOOR GRES


Serie / Series / Kolekcja / Serija	CEN/TS 16165:2012 Annex B $\alpha_{SHOD}$	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
B&W Marble Magnum glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
B&W Marble Magnum matte	$\alpha$ da 6° a 10°	>0,4	R9	N.P.D.
BUILDTECH 2.0 Magnum naturale	$\alpha$ da 6° a 10°	>0,4	R9	N.P.D.
BUILDTECH 2.0 Magnum R+PTV	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
BUILDTECH Magnum levigato	N.P.D.	N.P.D.	N.P.D.	N.P.D.
FLOWTECH Magnum naturale	$\alpha$ da 6° a 10°	N.P.D.	R9	N.P.D.
FLOWTECH Magnum R+PTV	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
INDUSTRIAL Magnum naturale	$\alpha$ da 6° a 10°	N.P.D.	R9	N.P.D.
INDUSTRIAL Magnum R+PTV	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
RAWTECH MAGNUM	$\alpha$ da 6° a 10°	>0,4	R9	N.P.D.
RAWTECH Magnum R+PTV	$\alpha$ da 11° a 19°	>0,4	R10	N.P.D.
STONTECH 4.0 magnum high-glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
STONTECH 4.0 magnum matte	N.P.D.	>0,4	N.P.D.	N.P.D.



FLORIM CERAMICHE S.p.A. a socio unico  
VIA CANALETTO 24 / 41042 FIORANO MODENESE (MO) ITALY  
T. +39 0536 840111 / F. +39 0536 840322  
[www.florim.com](http://www.florim.com)

# CE MARKING

Fine porcelain stoneware SLIM/4  
Coloured body porcelain stoneware SLIM/4  
Fine porcelain stoneware MAGNUM

	
<b>FLORIM CERAMICHE S.p.A.,</b> <b>Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia</b>	
09 FLORIM 003	
<b>EN 14411:2012</b> Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$ , for internal and external walls and floorings	
<b>Reaction to fire</b>	A1 <sub>FL</sub> /A1
<b>Release of dangerous substances, for:</b>	
- Cadmium	NPD
- Lead	NPD
<b>Breaking strength</b>	> 700 N
<b>Slipperiness, as:</b>	See table attached
<b>Tactility</b>	NPD
<b>Bond strength/adhesion, for:</b>	
Cementitious adhesive, type C2	NPD
<b>Thermal shock resistance</b>	Pass
<b>Durability, for:</b>	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass