

statements | TILE & STONE

Jewel Slab

Porcelain Slab

Thickness: 6mm

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≤0.1%
Break Strength	C648	ISO-10545/4	S≥1,300 N R≥50 N/mm ²
Scratch Hardness	MOH's Scale	EN-101	5
Chemical Resistance	C650	ISO-10545/13	A LA
Frost Resistance	C1026	ISO-10545/12	Resistant
Stain Resistance	C1378	ISO-10545/14	5
Fire Rating	E84	ISO-13501/1	Non Combustable
Deep Abrasion-Unglazed Tiles	C1243	ISO-10545/6	<150mm ³
PEI-Abrasion Resistance of Glazed Tile	C1027	ISO-10545/7	**
Shade and Texture Rating	CTDA "V"	-	V2
Facial Dimensions	C499	ISO-10545/2	Compliant
Range of Thickness	C499	ISO-10545/2	Compliant
Warpage/Surface Flatness	C485	ISO-10545/2	Compliant
Wedging/Rectangularity	C502	ISO-10545/2	Compliant

** PEI 3 - Raymi, Moonless
PEI 4 - Extra White

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188