LUMINOUS BEAM ASH GRAY (H&P) Marble, Stone



PART NUMBER
MB1809-DS0800
availability In Stock
DIMENSIONS 8'' x 8'' = .444 sqft
THICKNESS

3/8"

PROFILE MOSAICS

GROUT JOINT BUTT JOINT

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS BEAM CALACATTA (H&P) Stone, Marble



PART NUMBER	Profile
MB1203-DS0801	Mosaics
availability	VARIATION
In stock	HIGH
DIMENSIONS	grout joint
8'' x 8'' = .444 sqft	butt joint
THICKNESS	SEALER
3/8"	YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when sealed properly.	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS BEAM CARRARA (H&P) Stone, Marble



PART NUMBER	Profile
MB1130-DS08H0	Mosaics
availability	VARIATION
In stock	MEDIUM
DIMENSIONS	GROUT JOINT
8'' x 8'' = .444 sqft	BUTT JOINT
THICKNESS	SEALER
3/8"	YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	Specification	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS BEAM THASSOS W/ SILVER (H) Stone, Marble, Mixed Media



PART NUMBER MB1232-DS08H0
availability In stock
DIMENSIONS 8'' x 8'' = .444 sqft
THICKNESS 3/8"

PROFILE MOSAICS GROUT JOINT BUTT JOINT SEALER

YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1
Heat Resistance	Heat not to exceed 293° F	96/603/CE

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS BEAM CALACATTA W/ GOLD (H) Marble, Stone, Mixed Media



PART NUMBER MB1203-DS0800
availability In stock
DIMENSIONS 8'' x 8'' = .444 sqft
THICKNESS

PROFILE
MOSAICS
GROUT JOINT BUTT JOINT
SEALER

YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when sealed properly.	No	No

3/8"

TECHNICAL DATA

FEATURES	Specification	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1
Heat Resistance	Heat not to exceed 293° F	96/603/CE

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

LUMINOUS DAYBREAK ASH GRAY (H & COMBED) Marble, Stone



Part Number Mb1809-daybh0

availability In stock

DIMENSIONS

THICKNESS 3/8"

8.11'' x 10.43'' = .588 sqft

Profile Mosaics

GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS DAYBREAK CALACATTA (H & COMBED) Stone, Marble



Part NUMBER	Profile
MB1203-DAYBH1	Mosaics
availability	VARIATION
In stock	HIGH
DIMENSIONS	GROUT JOINT
8.25'' x 10.5'' = .588 sqft	1/16"
THICKNESS	SEALER
3/8"	YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when sealed properly.	No	No

TECHNICAL DATA

FEATURES	Specification	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS DAYBREAK CARRARA (H & COMBED) Stone, Marble



PART NUMBER	PROFILE
MB1130-DAYBHO	MOSAICS
availability In stock	VARIATION MEDIUM
DIMENSIONS 8.25'' x 10.5'' = .588 sqft	GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS DAYBREAK THASSOS W/ SILVER (H) Stone, Marble, Mixed Media



PART NUMBER	PROFILE
MB1232-DAYBHO	MOSAICS
availability In Stock	GROUT JOINT 1/16"
DIMENSIONS 8.25'' × 10.5'' = .588 sqft	SEALER YES
THICKNESS 3/8"	

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	Specification	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1
Heat Resistance	Heat not to exceed 293° F	96/603/CE

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS DAYBREAK CALACATTA W/ GOLD (H) Stone, Marble, Mixed Media



MB1203-DAYBHO
AVAILABILITY
DIMENSIONS 8.25'' x 10.5'' = .588 sqft
0.25 × 10.5 = .500 sqli
THICKNESS
3/8"

PROFILE MOSAICS GROUT JOINT 1/16" SEALER

YES

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when sealed properly.	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1
Heat Resistance	Heat not to exceed 293° F	96/603/CE

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

LUMINOUS SHINE ASH GRAY (H&P) Stone, Marble



PART NUMBER
MB1809-SHNEHO

AVAILABILITY

THICKNESS 3/8"

DIMENSIONS 7.72'' x 8.89'' = .37 sqft PROFILE MOSAICS

GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS SHINE CALACATTA (H&P) Stone, Marble



PART NUMBER
MB1203-SHNEHO

AVAILABILITY

THICKNESS 3/8"

IN STOCK DIMENSIONS 7.72'' x 8.89'' = .37 sqft PROFILE MOSAICS

GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS SHINE CARRARA (H&P) Stone, Marble



PART NUMBER	
MB1130-SHNEHO	
AVAILABILITY	
IN STOCK	

DIMENSIONS 7.72'' x 8.89'' = .37 sqft THICKNESS

3/8"

Profile Mosaics

GROUT JOINT

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS SHINE THASSOS W/ SILVER (H) Stone, Marble, Metallic



PART NUMBER MB1232-SHNEHO

AVAILABILITY

DIMENSIONS 7.72'' x 8.89'' = .37 sqft THICKNESS

3/8"

PROFILE MOSAICS

GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Heat Resistance	Heat not to exceed 293° F	96/603/CE

LUMINOUS SHINE CALACATTA W/ GOLD (H) Stone, Marble, Metallic



PART NUMBER MB1203-SHNEH1

AVAILABILITY

DIMENSIONS

THICKNESS 3/8"

7.72'' x 8.89'' = .37 sqft

MOSAICS

PROFILE

GROUT JOINT 1/16"

environments

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Heat Resistance	Heat not to exceed 293° F	96/603/CE

LUMINOUS RISE ASH GRAY (H & COMBED) Stone, Marble



PART NUMBER MB1809-RISEHO

availability In stock

DIMENSIONS 11.02'' x 11.77'' = .90 sqft

THICKNESS 3/8" PROFILE MOSAICS

GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS RISE CALACATTA (H & COMBED) Stone, Marble



PART NUMBER MB1203-RISEHO

AVAILABILITY

Profile Mosaics

GROUT JOINT 1/16"

DIMENSIONS 11.02'' x 11.77'' = .90 sqft THICKNESS

3/8"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS RISE CARRARA (H & COMBED) Stone, Marble



PART NUMBER MB1130-RISEHO

AVAILABILITY

DIMENSIONS 11.02'' x 11.77'' = .90 sqft THICKNESS

3/8"

PROFILE MOSAICS

GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS RISE THASSOS W/ SILVER (H & COMBED) Stone, Marble, Metallic



PART NUMBER MB1232-RISEHO

AVAILABILITY

MOSAICS GROUT JOINT

PROFILE

1/16"

DIMENSIONS 11.02'' x 11.77'' = .90 sqft THICKNESS

3/8"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Heat Resistance	Heat not to exceed 293° F	96/603/CE

LUMINOUS RISE CALACATTA W/ GOLD (H & COMBED) Stone, Marble, Metallic



PART NUMBER MB1203-RISEH1

AVAILABILITY

DIMENSIONS 11.02'' x 11.77'' = .90 sqft

THICKNESS 3/8" PROFILE MOSAICS

GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Heat Resistance	Heat not to exceed 293° F	96/603/CE

LUMINOUS RAY ASH GRAY (H & P & COMBED) Marble, Stone



PART NUMBER
MB1809-RAYOHO

AVAILABILITY

SLAB GROUT JOINT 1/16"

PROFILE

DIMENSIONS 10.19'' x 9.75'' = .689 sqft

THICKNESS 3/8"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

LUMINOUS RAY CALACATTA (H & P & COMBED) Stone, Marble



PART NUMBER	PROFILE
MB1203-RAYOH1	MOSAICS
availability In Stock	VARIATION HIGH
DIMENSIONS 10.19'' x 9.75'' = .689 sqft	GROUT JOINT
	1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when sealed properly.	No	No

TECHNICAL DATA

FEATURES	SPECIFICATION	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS RAY CARRARA (H & P & COMBED) Stone, Marble



PART NUMBER	PROFILE
MB1130-RAYOHO	MOSAICS
availability In stock	VARIATION MEDIUM
DIMENSIONS 10.19'' x 9.75'' = .689 sqft	GROUT JOINT 1/16"

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	Yes	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	Specification	STANDARD
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS RAY THASSOS W/ SILVER (H & COMBED) Stone, Marble



PART NUMBER	PROFILE
MB1232-RAYOHO	MOSAICS
availability	GROUT JOINT
In stock	1/16"
DIMENSIONS	SEALER
10.19'' x 9.75'' = .689 sqft	YES
THICKNESS 3/8"	

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when properly sealed	No	No

TECHNICAL DATA

FEATURES	Specification	standard
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1
Heat Resistance	Heat not to exceed 293° F	96/603/CE

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.

IT IS IMPORTANT TO PROPERLY SEAL MARBLE USED IN A SHOWER/STEAM SHOWER, AND MAINTAIN THE SEALANT REGULARLY TO ENSURE WATER BEADS OFF THE TILE.

LUMINOUS RAY CALACATTA W/ GOLD (H & COMBED) Stone, Marble, Mixed Media



PART NUMBER	PROFILE
MB1203-RAYOHO	MOSAICS
availability	GROUT JOINT
In Stock	1/16"
DIMENSIONS	SEALER
10.19'' x 9.75'' = .689 sqft	YES
THICKNESS 3/8"	

ENVIRONMENTS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	REPEAT
Yes	No	Yes	No	No	Yes, when sealed properly.	No	No

TECHNICAL DATA

FEATURES	Specification	standard
Frost resistance	No	UNE-EN-ISO-10545-12
DCOF		ANSI A137.1
Heat Resistance	Heat not to exceed 293° F	96/603/CE

DUE TO THE INHERENT CHARACTERISTICS OF NATURAL STONE, THERE MAY BE VARIATIONS IN COLOR, MOVEMENT AND TEXTURE FROM LOT TO LOT.