

statements | TILE & STONE

Marvel X Slab

Porcelain Slab

Thickness: 6mm

of Faces: 4 Faces

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≤0.1%
Break Strength	C648	ISO-10545/4	S ≥1000 N R ≥40 N/mm ²
Scratch Hardness	MOH's Scale	EN-101	5
Chemical Resistance	C650	ISO-10545/13	A LA HA
Frost Resistance	C1026	ISO-10545/12	Resistant
Stain Resistance	C1378	ISO-10545/14	5
Fire Rating	E84	ISO-13501/1	Non Combustible
Deep Abrasion-Unglazed Tiles	C1243	ISO-10545/6	≤ 150 mm ³
Dynamic Coefficient of Friction (DCOF)	A137.1	-	≥ 0.42
Shade and Texture Rating	CTDA "V"	-	V2 (Cal. Apuano) V3 (all other colors)
Facial Dimensions	C499	ISO-10545/2	Pass
Range of Thickness	C499	ISO-10545/2	Pass
Warpage/Surface Flatness	C485	ISO-10545/2	Pass
Wedging/Rectangularity	C502	ISO-10545/2	Pass

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188