

# statements | TILE & STONE

## Wanderlust

Porcelain Slab

Thickness: 6mm

	ASTM Test	ISO Test	Specifications
Water Absorption	C373	ISO-10545/3	≤ 0.1%
Break Strength	C648	ISO-10545/4	S ≥ 1.300 N R ≥ 50 N/mm <sup>2</sup>
Scratch Hardness	MOH's Scale	EN-101	5
Frost Resistance	C1026	ISO-10545/12	No Damage
Stain Resistance	C1378	ISO-10545/14	5
Deep Abrasion-Unglazed Tiles	C1243	ISO-10545/6	< 150 mm <sup>3</sup>
PEI-Abrasion Resistance of Glazed Tile	C1027	ISO-10545/7	**
Shade and Texture Rating	CTDA "V"	-	V2
Facial Dimensions	C499	ISO-10545/2	Complying
Range of Thickness	C499	ISO-10545/2	Complying
Warpage/Surface Flatness	C485	ISO-10545/2	Complying
Wedging/Rectangularity	C502	ISO-10545/2	Complying

\*\*PEI: WA 01 - 5  
 WA 02, 03, 05-08 - 3  
 WA 04, 09, 10 - 4

Statements Tile & Stone

17600 W Valley Hwy

Tukwila, WA 98188